

Avery Dennison® Monarch® Pathfinder® 6032 Printer

SCAN, PRINT AND APPLY - IT'S THAT SIMPLE

The Avery Dennison® Monarch® Pathfinder® 6032 printer is perfect for automating small volume labeling applications.

Combining scanning, printing or offline key entry and applying processes into a unique one-piece handheld solution, you can achieve faster markdowns and promotional labeling at retail or inventory management within manufacturing and distribution.

Durable plastic and rubber over-molds help protect the printer when dropped.

BENEFITS OF MOBILE PRINTING

- **Print Labels On-Demand.** Labeling at the product eliminates process steps and trips to the backroom for pre-printed labels
- **Improve Inventory Accuracy.** Eliminate mistakes due to unreadable markdowns or routing label mismatches at the carton. Using the Pathfinder 6032, associates are able to perform markdown and promotional labeling with greater speed and accuracy than conventional red-pen or hand applied labeling techniques
- **Labeling Completed On Time.** Labeling events are streamlined and completed on-time, the first time, with less associate handling*

ELEVATING BRANDS. ACCELERATING PERFORMANCE.

For more information call: 800.543.6650, prompt 5 or email: printesolutions@averydennison.com



Innovative, intelligent and sustainable labeling and printing solutions that accelerate supply chain performance, increase productivity and elevate the consumer experience.

*Based on results from internal time studies

SPECIFICATIONS

DIMENSIONS

Height - 6.5" (165mm) Width - 7.75" (197mm)
 Depth - 3.25" (83mm) Weight - 1.973 lbs (0.90kg)
 Shipping Wt. - 4.09 lbs (1.86kg)

PRINTING METHOD

Thermal Direct

PROCESSOR SPEED

40 MHz

MEMORY

RAM: 4MB
 Flash: 4MB

BAR CODES

UPCA, UPCA+2, UPCA+5, UPCA+Price CD, UPCE, UPCE+2, UPCE+5, EAN8, EAN8+2, EAN8+5, EAN13, EAN13+5, EAN13+Price CD, Interleaved 2 of 5, Interleaved 2 of 5 with Barrier Bar, Code 39, Codabar, Code 128, Code 93, MSI, GS1 Databar, PDF417, Maxicode, Code 16K, Data Matrix, RSS, Quick Response (QR), Postnet, GS1 Databar

STANDARD FONTS

Standard, Reduced, Bold, OCR-A-like, EFF Swiss Bold, HR1 and HR2 (numeric only), scalable fonts in Bitmapped and TrueType®, International Fonts

FONT MAGNIFICATION

1X to 7X for Bitmapped fonts, 4 to 250 pt. for scalable/TrueType® fonts

SENSING METHOD

Black mark

KEYPAD DISPLAY

25 keys, including on/off alpha/numeric supported; 2-line 15 character with backlight display

PRINTER CONTROL LANGUAGE

MPCL

PRINTER WARRANTY

One (1) year parts and labor. Full written warranty statement available on request.

PRINthead WARRANTY

One (1) million inches or six months, whichever comes first

SUPPLIES

Only Avery Dennison supplies are recommended. Use non-perforated supplies in peel mode, butt cut, die cut or non-indexed.

SUPPLY TYPES

Labels, tags and receipt paper

SUPPLY SIZES

Width: 1.1" to 2.0" (27.94mm to 50.8mm)
 Length: 0.55" to 4.0" (13.97mm to 101.6mm)
 Length with apply: 0.785" (19.939mm)

SUPPLY ROLL SIZES

Width: 2.5" on a 1" core (63.5mm on a 25.4mm core)

TYPICAL SUPPLY ROLL LENGTH

420" to 580" (10.7m to 14.7m)

SUPPLY THICKNESS

Tags - 0.007" (.017mm)
 Labels - 0.0024" (.0609mm)



MAXIMUM PRINT AREA

1.89" x 3.837" (48mm x 97.46mm)

RIBBON LENGTH

N/A

ENVIRONMENTAL RANGES

OPERATING TEMPERATURES

40° to 110°F (4° C to 43° C)

STORAGE

N/A

HUMIDITY/OPERATING AND STORAGE

5% to 90% non-condensing

ELECTROSTATIC DISCHARGE AND AIR QUALITY

Some problems with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Avery Dennison suggests that you take precautions to minimize these

IP RATING

N/A

PERFORMANCE

POWER SOURCE

Battery

PRINT RATIO

25%

INCHES PER CHARGE

5,000 inches of 2" X 2" stock

BATTERY LIFE CYCLE

300 full discharge cycles. Many factors affect individual battery performance

RECOMMENDED DUTY CYCLE

33% duty cycle for continuous printing (5 minutes out of 15-minute time intervals). On demand or intermittent printing has no restrictions.

PRINT SPEED

2.0 IPS

COMMUNICATIONS

STANDARD COMMUNICATION PORTS

RS-232-C

WIRED NETWORKING

N/A

OPTIONS AND ACCESSORIES

OPTIONS

- 802.11 a/b/g/n dual band
- Integrated 2D or 1D scanner

ACCESSORIES

- Battery (part#12009502) 9465™ four-station battery charger
- 9462™ single station battery charger
- Deluxe hand strap (part#130606)
- USB cable
- 6055/6054 communication/charging/docking station
- Shoulder strap (part#130605)
- Deluxe padded wrist strap (part#130604)

AMERICAS

170 Monarch Lane
 Miamisburg, OH 45342
 937 865 2123 (direct)
 Tel +800 543 6650
 (8:00 a.m.–6:30 p.m., EDT)
 Fax +937 865 6663

ASIA

No. 7 Chun Ying Street
 Tseung Kwan O Industrial Estate
 New Territories, Hong Kong
 Tel +852 2372 3169
 Fax +852 2995 0014

WESTERN EUROPE

1 Thomas Road
 Wooburn Green
 Bucks HP10 0PE
 Tel +(44) 1628 859500
 Fax +(44) 1628 859567

ASIA PACIFIC NEW SOUTH WA

61 Vore Street
 Silverwater NSW 2128
 Tel +(02) 9647 1833
 Fax +(02) 9647 1914
 Toll free (Outside Sydney only)

Accelerating supply chain performance and elevating the consumer experience.

AVERY DENNISON® SERVICE AND SUPPORT

Our technical specialists and service representatives can provide installation support, training and operating recommendations. For more information call 800.543.6650, option 7.